



OVERVIEW

Time synchronization creates a platform for an entire system comprising wide range of applications to operate in synchronous with time.

The demand for improving the effectiveness of any system in place is met with time synchronization system deployed in the field. Troubleshooting is simplified by the application of time synchronization in the event of fault analysis.

SERTEL manufactures GNSS based Time Synchronization System which generates precise time stamp signals that synchronizes various network of electrical, computer, communications devices such as DCS, PLCs, LANs, Computer Buses, RTUs etc.

Equipped with high precision and high stability Oscillators*, T-GPS-300-S09 is capable of performing with greater accuracy and tenacity during temporary signal loss.

The time stamps in the signal could be transmitted over long distances maintaining synchronization in the whole network.

OPERATION

The signal from the satellite is collected by T-GPA-014-S15, an active antenna and transmits the signal to T-GPS-300-S09 GPS Receiver.

Time base pulses as that in the UTC or the atomic clock in the GPS satellites are generated.

Master Clock is provided for continuous functioning of the system.

Pulses can be generated for every second, minute, ½minute, hour, day etc which are configurable.

LC display upfront shows the frequency, date, time and geographical location. These can be viewed with the help of keypad upfront.

Status LED indication can also be seen displaying the operating conditions of the receiver.

Highly precise and stable Oscillator Time keeping compensates for any interferences or loss of signal from the satellite thus making the operation of the receiver reliable

KEY FEATURES

- Compact size & Easy usability
- Multi Constellation Channel GNSS Receiver and minimum 12 Channel Continuous Tracking.
- Equipped with high precision OCXO crystal for frequency maintaining micro second level accuracy.
- Accuracy of 14 nano second with GNSS Signal.
- LCD Display: 2x16 / 2x20 characters
- Highly customizable Output configurable as per requirement.
- Configured to work as Stand-Alone Time server.
- Universal Power Supply.
- Drives a number of Slave Clocks / Digital Clocks.
- Provides time/ date stamping through Ethernet, Coaxial & Serial interfaces.
- Low-cost maintenance with durable performance.

T-GPS-300-S09
GPS TIME SYNC SERVER



SERTEL ELECTRONICS PVT LTD
Old Mahabalipuram Road, Perungudi, Chennai, Tamilnadu, India 600 096.
Ph: +91(44)23454060, +91(44)23454062
sales@sertelelectronics.com



SERTEL ELECTRONICS UK LTD
Rutland House, 148 Edmund Street, Birmingham, B3 2FD, UK
Ph: +44 (0) 121 661 6479
enquiryuk@sertelserver.com



SERTEL INSTRUMENTS INC
Saskatoon, Saskatchewan Canada

GPS TIME SYNC SERVER

T-GPS-300-S09

TECHNICAL SPECIFICATIONS

GPS ANTENNA

Model	T-GPA-014-S15
Receiving Frequency	L1- 1575.42 MHz L5- 1176 Mhz
Tracking code	'L' Band CA code
Geodetic System	WGS – 84
No. of Channels	24 Channel / Parallel
Type	Helical
Axial Ratio	<4 dB
Supply Voltage	+5V DC (Internal)
Gain	Over 40 dB
Noise Figure	Less than 0.5 dB
Operating Temp	-40 °C to +85 °C
Connector	BNC
Dimension	80(h)x55(d) x 82(w) mm
Mounting	Fixed (Roof mount) IP67 (Ingress Protection Rating)

ENVIRONMENT

Storage Temperature	-40 to +85 °C
Operating Temperature	-10 to +55 °C
Humidity	0 – 95% RH, non-condensing

GPS RECEIVER

Model	T-GPS-300-S09
Interface	TTL (Normal High)
Input connector	BNC
Output Rate	Every second
Power Supply	90-260 V AC/DC A & B
Display	2x16 / 2x20 LCD
Type	GPS: L1 C/A, L2C, GLO: L1OF, L2OF, GAL: E1B/C BDS: B1I, B2I 184 Channel Parallel-tracking receivers
Frequency	L1 & L2
Sensitivity (Acquisition)	-148 dBm
Sensitivity (Tracking)	-167 dBm
Design	1U rack-mount bracket designed for 19 Inch Cabinets Fabricated Heatsinks
Protocol	NMEA, Sertel Format, Serial String ASCII format.

MECHANICAL SPECIFICATION

Dimensions	1U(H) x 485(W) x 185(D) mm (Or) 2U(H) x 485(W) x 325(D) mm *Size Depends on number of outputs
Mounting	19" Rack
Weight	2.5 KG



SERTEL ELECTRONICS PVT LTD

Old Mahabalipuram Road, Perungudi,
Chennai, Tamilnadu, India 600 096.
Ph: +91(44)23454060, +91(44)23454062
sales@sertelelectronics.com



SERTEL ELECTRONICS UK LTD

Rutland House, 148 Edmund Street,
Birmingham, B3 2FD, UK
Ph: +44 (0) 121 661 6479
enquiryuk@sertelserver.com



SERTEL INSTRUMENTS INC

Saskatoon,
Saskatchewan Canada

Power Drain

45W *Depends on Output configuration

Power Supplies	1x or 2x Power Supplies High Voltage - AC/DC 90-370 VDC 80-260 VAC Low Voltage - DC 24-60 VDC <small>*Feature Available only on Specific requests and suitable price points</small>
----------------	---

Ingress Protection IP40

Configuration Software

Platform HTTPS/SSL Browser-based configuration

INPUT

GNSS Antenna inputs	L1Band GNSS, BNC [F]
Configuration	Sertel Time Management Suite for complete accessibility and configurability of server. Keypad for local configuration L1Band GNSS, BNC [F] <small>*Feature Available only on Specific Requests and suitable price points</small>
Input	DC IRIG-B Input (BNC)
Antenna Input	BNC 5V GNSS Input
Alarm Relay	3-Pin Form-C NO/NC alarm relay

NETWORK TIME SERVER OPTION*

IEEE 1588v2 (PTP)	P2P/E2E delay 1-Step/2-Step delay C37.238:2011 Power Profile C37.238:2017 Power Profile ITU G.8265.1 Telecom Profile ITU G.8275.1 Telecom Profile IEEE 61850-9-3 Power Utility Profile
NTP/SNTP	Stratum 1 NTP & SNTP Time server Multicast & Broadcast capability

Oscillator Options

*Feature Available only on Specific requests and suitable price points

Disciplined Oscillator	TBC*
Rubidium	TBC*
VCTCXO	TBC*
OCXO	TBC*

OUTPUT VARIANTS*

1PPS	TTL, 50 Ω Impedance, BNC [F]
IRIG-B	AM [B125], 50 Ω Impedance Sine Wave, BNC [F] TTL [PWM]
DCF77	TTL, 50 Ω Impedance, BNC [F]
Pulse Outputs	1 PPM/PPS/PPD/PPH/ Configurable
Display Outputs	Differential Pulse/ Serial/ IRIGB
Fiber Output PPS NTP IRIGB TTL	ST Fiber 62.5/125 μm, λ 820 nm
Programmable Output	TTL or Frequency Output (1.544, 2.048, 10MHz, Sine or Square) (BNC) TTL or AM IRIG-B Output (BNC) TTL Input/Output (BNC) ST Fiber (62.5/125 μm) multi-mode HV MOSFET 300V 1A (2-pin) Modbus RS485/TCPIP IEC60870-103/104
Ethernet Output	RJ45 - Time Protocols NTP, PTP
Ethernet Connections	RJ45 1GbE/Fast Ethernet SFP 1GbE/Fast Ethernet <small>*Feature Available only on Specific Requests and suitable price points</small>



SERTEL ELECTRONICS PVT LTD
Old Mahabalipuram Road, Perungudi, Chennai, Tamilnadu, India 600 096.
Ph: +91(44)23454060, +91(44)23454062
sales@sertelelectronics.com



SERTEL ELECTRONICS UK LTD
Rutland House, 148 Edmund Street, Birmingham, B3 2FD, UK
Ph: +44 (0) 121 661 6479
enquiryuk@sertelserver.com



SERTEL INSTRUMENTS INC
Saskatoon, Saskatchewan Canada

SNMP V1, V2C & V3 support can be independently enabled
Configurable V1, V2C community names & security groups
Fully monitored via SNMP;

Protocols supported	ARP, UDP, ICMP, DHCP, SNMP, HTTPS, IPv4, IPv6
---------------------	---

CLOCK ACCURACY TO UTC

TTL/Fiber:	< 100 ns	AM IRIG-B	< 100 ns
PTP Time Stamp	< 100 ns	1 PPS	< 100 ns
Security	User-Defined Access Control Lists (ACL)	NTP Timestamp at Server Source	< 1 μ s (At client End Depends on Network Architecture for more accuracy)
PRP	IEC 62439-3 (2016) Fast failover slave Supports up to two PRP pairs PTP (IEEE 1588v2) Default & Power Profiles	Notifications *Feature Available only on Specific Requests and suitable price points	SNMP trap generation V1, V2C & V3 SNMPv3 traps can be authenticated Syslog (RFC-3164 & 5424 verities)

TEST AND STANDARDS

Dry Heat Test	IEC 60068-2-2	Electrostatic Discharge Immunity Test	IEC 61000-4-2,2008
Cold Test	IEC 60068-2-1	Radiated Susceptibility Test	IEC 61000-4-3,2010
Damp Heat (Steady State) Test	IEC 60068-2-3	Electrical Fast Transient Immunity	IEC 61000-4-4,2012
Sinusoidal Vibration Test	IEC 60068-2-6	High Energy Surge Immunity Test	IEC 61000-4-5,2014
Dielectric Strength Test	IEC 60255-5-0	Conducted RF Immunity Test	IEC 61000-4-6,2013
Pulse Magnetic Field Test	IEC 61000-4-9,2016	Power Frequency Magnetic Field Test	IEC 61000-4-8,2009
Radiated RF Power Disturbance	CISPR 14-1,2009	Damped Oscillatory Sinusoidal Immunity Test	IEC 61000-4-18,2011
Voltage Fluctuation and Flicker Emission Test	IEC 61000-3-3,2013	Voltage Dips and Interruption Immunity Test	IEC 61000-4-11
Harmonics, Inter Harmonics and Low Frequency Immunity Test	IEC 61000-4-13,2002		

*Feature Available only on Specific requests and suitable price points
*Output ports are customizable based on the requirements
*Product development is continuous process, subject to change without prior notice



SERTEL ELECTRONICS PVT LTD

Old Mahabalipuram Road, Perungudi, Chennai, Tamilnadu, India 600 096.
Ph: +91(44)23454060, +91(44)23454062
sales@sertelelectronics.com



SERTEL ELECTRONICS UK LTD

Rutland House, 148 Edmund Street, Birmingham, B3 2FD, UK
Ph: +44 (0) 121 661 6479
enquiryuk@sertelserver.com



SERTEL INSTRUMENTS INC

Saskatoon, Saskatchewan Canada